

## PRO151T Monitor

### 15" Touchscreen LCD Display

- Contaminant resistance and high touch responsive
- Contrast ratio of 350:1, brightness of 250cd/m<sup>2</sup>
- Panel Thickness of 2.0mm and Surface Hardness of 3H
- VESA mounting capability

[Image Gallery](#)

[Add To Cart](#)



PROLINK® **PRO151T** Touchscreen is a high performance intelligent multi-scanning color monitor. It is with 15" TFT LCD screen and MCU digital control without radiation and glare, offers simply outstanding image sharpness, vibrant colors and high contrast tones with resolution of 1024 x 768 pixels.

PRO151T is act as both an input and output device, using a graphical user interface (GUI) there is no need for a separate monitor, keyboard and mouse as the touchscreen monitor acts as all three.



#### VESA Standard Compliant

VESA standard compliant can be easily attached to any of touch panel mounts and brackets, covering the entire range of mounting options, including desktop, wall, mobile and ceiling mounts.

- Sleek and slim, lightweight touch panel design, adapting to small places to saving more space for your workstations.
- Anti-glare, scratch proof and super clear touchscreen.
- Ideal for kiosk integrators, VARs and OEMs in healthcare, retail, POS or hospitality applications.
- Resistive technology and touch accuracy of >99%.
- Low power consumption for reduced total cost of ownership.

**Picture /Display**

- Panel Size: 15 inch Diagonal Analog RGB
- Max Resolution: 1024 x 768 Pixels
- Display Area: 304.1(H) x 228.1(V) mm
- Dot Pitch: 0.297 mm
- Brightness: 250cd/m<sup>2</sup>
- Contrast Ratio: 300:1 (typical)

- Response Time: 8ms

© 1991 - 2010 Fida International (S) Pte Ltd. All rights reserved.

All brand or product names are trademark or registered trademarks of their respective owners

- Viewing Angle: H=160°, V=130°
- H-Frequency: 30 ~ 60 kHz
- V-Frequency: 60 ~ 75 Hz

**Controls**

- On/Off, Menu, +/- Keys, Auto, Select
- OSD: PC Menu, Picture Menu

**Interface and Environmental**

- Glass Surface: Non-Glare Coating
- Connectors: Audio, Power Jack, D-Sub
- Basic I/O Ports: DC-12V, VGA D-Sub, DVI (Optional)
- Power Input: 100V - 260V, 50 / 60Hz
- Power Consumption: < 40W
- Power Saving: DMPS Power Saving < 5W
- Humidity: 10% ~ 90%
- Temperature: 0°C ~ 40°C
- Weight: 4.0 Kg
- Dimension: 430(L) x 1200(W) x 490(H) mm

\*\* Specifications in this datasheet are subject to change without prior notice.

Support resource temporary not available.

**Package Contents**

- PROLiNK® PRO151T 15" Touchscreen LCD Monitor
- 1 x VGA Cable
- 1 x Power Cord Cable
- User Manual